


## Miniature Polarization Scrambler Module



General Photonics' miniature polarization scrambler module, the PSM-002, is specially designed for integration into sensor and communication systems that need to work in extreme environmental conditions. The module uses General Photonics' patented fiber squeezer technology to effectively randomize polarization states. Unlike that of the PCD-005, the scrambling rate of this miniature scrambler is user selectable via an RS-232 command. Another attractive feature is that the scrambling function can also be enabled and disabled by a TTL trigger signal. The PSM-002 is available either

as a standard board for lab applications or fully enclosed in a water-tight enclosure for applications in high humidity environments. It also comes in either standard or extended temperature versions.

### Specifications:

Insertion Loss	< 0.05 dB (without connectors) < 0.6 dB (with connectors)
Operating Wavelength <sup>1</sup>	1260 to 1650 nm and 970 to 1300 nm standard
Output Degree of Polarization (DOP) <sup>2</sup>	< 5%, 2.5% typical
Average PMD	< 0.05 ps
Intrinsic PDL	< 0.05 dB, 0.01 dB typical
Return Loss	> 65 dB (without connectors)
Optical Power Handling	> 300 mW
Power Supply	5.0 – 5.5 VDC / 9 W max.
Power Consumption	0.5 – 9 watts, depending on the scrambling rate
Scrambling Rate	User selectable from 0.01 to 20,000 points/s
Operating Temperature	Standard: 0 to 65°C Extended: -35 to 70°C
Storage Temperature	-40 to 85 °C
Dimensions	3.78" × 2.5" × 0.7" (L × W × H), board version 4.53" × 3.25" × 0.75" (L × W × H), enclosure

#### Notes:

- Standard calibrated wavelengths are 1550nm (1260-1650nm version) and 1310nm (970-1300nm version). Others available.
- DOP specification is < 5% (to within 2σ) when averaged over 4000 or more points.

### Features:

- Works in extreme environmental conditions
- Minimal insertion loss and back reflection
- Low residual phase and amplitude modulation
- Selectable scrambling frequencies
- Small size (3.78" x 2.5" x 0.7")


### Applications:

- Sensor and communication systems
- Polarization sensitivity elimination
- Facilitating PMD emulation
- PMD monitoring for PMD compensation
- Facilitating PDL measurement

Tech Info: pp. 104, 215  
FAQ: p. 221

See page 43 for polarization scrambler with microprocessor controller, page 48 for micro scrambler, page 77 for passive depolarizer

### Ordering Information:



Wavelength Range:  
01 = 1260 - 1650 nm  
02 = 970 - 1300 nm

O = without enclosure  
E = with enclosure

Temperature Range:  
ST = standard  
ET = Extended

Connector Type:  
FC/PC, FC/APC, SC/PC, SC/APC, or  
NC = no connectors  
Others specify