

■ Specifications

Parameter		Unit	HSL-2100					
			Standard	High-speed	Wide range	High-linearity	High-speed Wide range	Large coherence
Wavelength scan *1	Center wavelength	nm	1315-1340	1315-1340	1290-1320	1315-1340	1300-1330	1315-1340
	Scan range	nm	≥ 110	≥ 80	≥ 170	≥ 110	≥ 140	≥ 30
Output power *2	Peak	mW	≥ 20	≥ 20	≥ 20	≥ 20	≥ 15	≥ 8
	Average	mW	≥ 12	≥ 12	≥ 10	≥ 12	≥ 9	≥ 5
Scan rate		kHz	20	50	20	20	50	3
Coherence length		mm	≥ 10	≥ 6	≥ 6	≥ 8	≥ 6	≥ 60
Duty cycle		%	≥ 65	≥ 90	≥ 60	≥ 60	≥ 65	≥ 40
Linearity (k-space)		%/100nm	-	-	-	0.25	-	-
Trigger			Integrated start trigger					
Output optical fiber			SMF					
Output optical connector			FC connector,APC polish					
Operation environment	Temperature	°C	15 - 35					
	Humidity	%	<80, no condensation					
Electric power			AC100V - 240V±10% , 50/60Hz					
Power consumption		VA	70 @ AC 100 - 120V, 80 @ AC 230 -240V					
Size (W) × (D) × (H)		mm	343 × 376 × 153					
Weight		kg	10					

Parameter		Unit	HSL-1100				
			Standard	High-speed	Wide range	Large coherence	High-speed Wide range
Wavelength scan *1	Center wavelength	nm	1045-1075	1045-1075	1045-1075	1045-1075	1045-1075
	Scan range	nm	≥ 70	≥ 70	≥ 120	≥ 20	≥ 80
Output power *2	Peak	mW	≥ 12	≥ 12	≥ 12	≥ 6	≥ 12
	Average	mW	≥ 8	≥ 8	≥ 5	≥ 4	≥ 5
Scan rate		kHz	30	50	20	3	50
Coherence length		mm	≥ 6	≥ 6	≥ 6	≥ 60	≥ 4
Duty cycle		%	≥ 65	≥ 90	≥ 60	≥ 40	≥ 90
Linearity (k-space)		%/100nm	-	-	-	-	-
Trigger			Integrated start trigger				
Output optical fiber			SMF (HI 1060 Fiber)				
Output optical connector			FC connector,APC polish				
Operation environment	Temperature	°C	15 - 35				
	Humidity	%	<80, no condensation				
Electric power			AC100V - 240V±10% , 50/60Hz				
Power consumption		VA	70 @ AC 100 - 120V, 80 @ AC 230 -240V				
Size (W) × (D) × (H)		mm	343 × 376 × 153				
Weight		kg	10				

\* Please note, these specifications are subject to change due to on-going engineering developments.

\* 1: Wavelength range of -10dB down from peak power

\* 2: Saw tooth waveform

■ Ordering Code

HSL-2100 -   
A

ST : Standard, HS : High-speed, WR : Wide range, HL : High-linearity, HW : High-speed Wide range, LC : Large coherence length

HSL-1100 -   
A

ST : Standard, HS : High-speed, WR : Wide range, HW : High-speed Wide range, LC : Large coherence length

www.santec.com E-Mail : sales@santec.com

2007 © SANTEC CORPORATION Santec reserves the right to make changes in equipment design, components or specifications without notice.



**SANTEC CORPORATION**  
 5823 Ohkusa-Nenjoyozaka, Komaki, Aichi 485-0802, Japan Tel. +81-568-79-1959 Fax +81-568-79-1718

**SANTEC U.S.A. CORPORATION**  
 433 Hackensack Ave., Hackensack, NJ 07601, U.S.A. Toll Free +1-800-726-8321(santec-1) Tel. +1-201-488-5505 Fax +1-201-488-7702

**SANTEC EUROPE LIMITED**  
 Magdalen Centre, Robert Robinson Ave., The Oxford Science Park, Oxford OX4 4GA, U.K. Tel. +44-1865-784960 Fax +44-1865-784961

**SANTEC (SHANGHAI) Co., Ltd.**  
 No.800 Zhangyang Road Changhang Tower, Pudong District, Shanghai 200122 China Tel: +86-21-58361261, +86-21-58361262 Fax: +86-21-58361263